



## Fast and highly accurate automatic tank calibration

- Tank calibration table is saved directly to sensor's memory (only for DUT-E, DUT-E GSM, DUT-E 2Bio, DUT-E S7, DUT-E 2Bio S7).
- Calibration control over Bluetooth using mobile app
- Speeds up tank calibration by 4-6 times.
- Three modes: automatic, semi-automatic, and continuous.
- "Human reliability" does not affect accuracy of calibration.
- Continuous operation throughout the entire workday.
- Compatible with fuel level sensors from any manufacturer.
- Autoshutdown in event of pressure/temperature excess.



Delivery set includes filling and suction hoses with camlock fittings.

### Example: calibration of 500-liter fuel tank

ATS, automatic mode:	10 minutes
Technician, calibration at gas station:	40 minutes
Technician, calibration with canister:	60 minutes

### Specifications

Tank calibration speed	3500 l/h
Relative inaccuracy of calibration	less than 0,5%
Power supply voltage	220/110 V
Dimensions (LxWxH)	72x36x23 cm
Weight of DUT-E ATS set*	23 ... 27 kg

\* delivery set includes suction hose, filling hose with fuel nozzle, fuel sensor cable extender.



phone: +420 910 122 429  
 e-mail: sales@jv-technoton.com  
 www.jv-technoton.com

